

Batteriehandel Zelltronik  
Jahnstraße 12  
72336 Balingen  
Tel. +49 7433/9975-181  
Fax: +49 7433/999072  
Email: info@akkuangebote.de



## CTL 55-12FT

### Datasheet

#### Innovative Features

Designed to meet the future needs of the Tele-communications industry for - mobile, wired, access, transmission, switching, integrated power applications etc.

Resulting in the following benefits to the customer:

- Compactness
- ETSI / 19" / 23" Integration
- Modularity
- Rackable Standard component
- Long life
- Use under extreme conditions
- High power volume ratio
- Maintenance free utilising VRLA technology
- Low Installation costs
- Front Connections and terminal access
- Long Design Life - 12 years
- Rope handles on 70Ah upwards
- Central gassing system and hinged front covers on all models
- Integral flame arrestor
- Low Internal resistance
- Recyclable lead and plastics
- Designed to meet BELLCORE, BS6290 Pt4, IEC896-2 recommendations
- Excellent Cycling ability
- Low self discharge rates



#### Specifications

Nominal Voltage	12 Volts
Design Life	12 Years
Operating Temperature	-20 °C to 50 °C
Grid alloy	Calcium / Tin lead alloy
Plates	Flat Pasted
Separator	AGM - Absorbant Glass Mat
Active material	Very high purity lead
Case and cover	ABS (VO on request)
Charge Voltage	Float 2.27 - 2.30 VPC @25 °C Cycling 2.35 @25 °C Max. 2.4 VPC Max ripple 0.05C (A)
Electrolyte	Sulphuric acid Analytical grade purity
Venting Valve	EPDM Rubber 1.5 to 2 psi (10.5 - 14 KPa) release pressure. Resealing at 1 psi (7 KPa)
Terminal	Epoxy sealed by extended mechanical paths
Torque setting	The recommended torque value is 5-7 Nm Connectors Supplied as standard



CTM GmbH keenly encourages environmental awareness; PLEASE follow guidelines for recycling/disposal of lead

[www.ctm-berlin.de](http://www.ctm-berlin.de)  
[info@ctm-berlin.de](mailto:info@ctm-berlin.de)

**We power the future.**

